

HYFLOW® COMMERCIAL VERTICAL MULTISTAGE PUMPS

FEATURES

The HYFLOW® Commercial range of vertical multistage pumps are designed for industrial, commercial and urban applications including; high rise apartments, shopping complexes, hospitals, industry processes, municipal water supply and irrigation. The pumps are an in-line design and have M.I.P (Maintenance In Place) capabilities.

- > 304 or 316 full stainless steel wet end pump construction
- > Efficient multistage impeller design for reduced running costs
- > Intermediate Tungsten carbide bearings for reduced vibration and long life
- > Silicon Carbide / Carbon mechanical seal, cartridge design for M.I.P capabilities
- > TEFC Motor Design
- > Fluid temperature range: -15°C to +120°C
- > Max pressure range: Variable depending on pump model
- > AS/NZS 4020 portable water compliant



30 YEARS INDUSTRY EXPERIENCE

RANGE

MODEL	POWER	MAX HEAD	FLOW	INLET / OUTLET
VM1-XX	0.37 - 1.1kW	2050kPa	0.66 l/sec	DN25/32 PN25
VM3-XX	0.37 - 3.0kW	2350kPa	1.2 l/sec	DN25/32 PN25
VM5-XX	0.37 - 5.5kW	2500kPa	2.3 l/sec	DN25/32 PN25
VM10-XX	0.37 - 7.5kW	2200kPa	3.6 l/sec	DN40 PN25
VM15-XX	1.1 - 16kW	2400kPa	6.5 l/sec	DN50 PN25
VM20-XX	1.1 - 18.5kW	2450kPa	8.0 l/sec	DN50 PN25
VM32-XX	1.5 - 30kW	2600kPa	11.0 l/sec	DN65 PN25
VM45-XX	3.0 - 45kW	3200kPa	16.0 l/sec	DN80 PN25
VM64-XX	4.0 - 45kW	2200kPa	23.5 l/sec	DN100 PN25
VM90-XX	5.5 - 45kW	2000kPa	33 l/sec	DN100 PN25
VM120-XX	11 - 75kW	2200kPa	44 l/sec	DN125 PN25
VM150-XX	11-75kW	2000kPa	50 l/sec	DN125 PN25

PERFORMANCE

