

TRADEWASTE OIL WATER SEPARATOR

OVERVIEW

The All Purpose Pumps Coalescing Oil Water Separator is the perfect solution for oil removal in vehicle wash bays, workshop facilities, industrial and service stations. Built in accordance with local water authority regulations.

FEATURES

SEPARATOR

- High efficiency, coalescing plate separator technology, removes oils and sand in a superior and efficient manner
- Polyethylene separator body construction
- Chemical resistant UV stabilised polyethylene thickness 5mm
- Sludge hopper
- Waste oil collection container

- Supplied as a complete package for fast and easy installation
- Environmentally friendly - safer than conventional methods
- Fast and easy periodic cleaning providing minimal maintenance requirements

PUMP AND CONTROLS

- For pump specifications contact All Purpose Pumps



RANGE

MODEL	STOCK CODE	FLOW	PUMP	L	W	H	INLET	OUTLET	DRAIN	POWER
OWS1000	808500126	1000l/hr	KDP25-100	1420mm	380mm	1470mm	32mm	50mm	50mm	240v 10amp
OWS1500	808500127	1500l/hr	KDP25-150	1420mm	690mm	1506mm	32mm	50mm	50mm	240v 10amp
OWS2000	808500128	2000l/hr	KDP32-200	1040mm	1110mm	1466mm	50mm	50mm	50mm	240v 10amp
OWS3000	808500129	3000l/hr	KDP38-300	1040mm	1110mm	1466mm	50mm	50mm	50mm	240v 10amp

NOTES

1. Systems can be customised to suit any application
2. All dimensions are in mm and are approximate

TYPICAL ARRANGEMENTS

